



Specification Sheet – SediMax-FR™ (Filtration Roll)

DESCRIPTION

SediMax-FR™ shall be a machine-produced 100% biodegradable sediment filtration system.

SediMax-FR shall be composed of 70% straw and 30% coconut fiber matrix evenly distributed over the entire area of the bottom netting. The SediMax-FR shall consist of a bottom netting and a 2 ft. (0.61 m) top netting that covers the matrix material on the “splash apron” of the SediMax-FR system. The netting shall be constructed from 100% biodegradable woven natural organic fiber netting. The netting shall consist of machine directional strands formed from two intertwined yarns with cross directional strands interwoven through the twisted machine strands (commonly referred to as a Leno weave) to form an approximate (0.50 x 1.0 inch (1.27 x 2.54 cm) mesh. The blanket shall be sewn together on 1.50 inch (3.81 cm) centers with biodegradable thread.

Each SediMax-FR shall yield a structure 50 linear feet (15.2 m) in length, with an approximate finished diameter of 9 inches (0.23 m). The diameter of the finished structure may be increased to meet individual project specifications by spreading loose straw, pine needles, wood chips, grass clippings, etc. across the width of the SediMax-FR before rolling edge to edge.

Material Content		
Matrix	70% Straw Fiber	1.225 lbs/sy (0.665 kg/sm)
	30% Coconut Fiber	0.525 lbs/sy (0.285 kg/sm)

Netting	Bottom: Leno woven 100% biodegradable natural organic Fiber	9.30 lbs/1000 sf (4.50 kg/ 100 sm)
	Top: 2 ft (0.61 m) strip covering the “splash apron”, Leno weave jute netting	9.30 lbs/1000 sf (4.5 kg/100 sm)

Thread	Biodegradable
---------------	---------------

Physical Specifications	
Width	6.67 ft (2.03 m)
Length	50.00 ft (15.25 m)
Weight +/- 10%	65.00 lbs (29.5 kg)
Stitch Spacing	1.5 in (3.81 cm)
Diameter	9.00 in. (0.23 m)



800-452-4435
info@jenhill.com
www.jenhill.com



Tensar International Corporation
2500 Northwinds Parkway
Suite 500
Alpharetta, GA 30009
800-TENSAR-1
tensarcorp.com

Tensar International Corporation warrants that at the time of delivery the product furnished hereunder shall conform to the specification stated herein. Any other warranty including merchantability and fitness for a particular purpose, are hereby executed. If the product does not meet specifications on this page and Tensar is notified prior to installation, Tensar will replace the product at no cost to the customer. **This product specification supersedes all prior specifications for the product described above and is not applicable to any products shipped prior to January 1, 2012.**

©2013, Tensar International Corporation

EC_SMX_MPD5_SEDI_FR_6.13