



Specification Sheet – SediMax-SW9™ (Straw Wattle 9 Inch)

DESCRIPTION

The SediMax-SW9 shall be composed of 100% agricultural straw and be wrapped in tubular UV stabilized synthetic net.

The netting weight shall be approximately 0.35 ounces/linear ft. and shall be made from HDPE (High Density Polyethylene) photodegradable oriented net with carbon black for UV inhibition. The netting shall have a diamond shaped aperture measuring 0.50 x 0.50 inches (1.27 x 1.27 cm).

The wattle ends will be secured with wire closures. SediMax-SW9 shall be installed according to manufacturer's recommendations. They shall be installed on contours and staked with 18 to 24 inch wood stakes at four foot on center.

Material Content		
Matrix	100% Straw Fiber	2.4 lbs/linear ft (3.54 kg/linear meter)
Netting	Tubular, diamond-shaped netting	0.35 oz/linear ft (30.0 g/linear meter)
Wire Closure	Industrial grade ring wire, 18 gauge	3.75 in (9.53 cm)

Physical Specifications	
Width	9.00 in (22.86 cm)
Length	25.00 ft (7.62 m)
Weight +/- 10%	60.00 lbs (27.22 kg)



800-452-4435
 info@jenhill.com
 www.jenhill.com



NORTH AMERICAN GREEN®

Tensar International Corporation
 2500 Northwinds Parkway
 Suite 500
 Alpharetta, GA 30009
 800-TENSAR-1
 tensarcorp.com

Tensar International Corporation warrants that at the time of delivery the product furnished hereunder shall conform to the specification stated herein. Any other warranty including merchantability and fitness for a particular purpose, are hereby executed. If the product does not meet specifications on this page and Tensar is notified prior to installation, Tensar will replace the product at no cost to the customer. **This product specification supersedes all prior specifications for the product described above and is not applicable to any products shipped prior to January 1, 2012.**

©2013, Tensar International Corporation

EC_SMX_MPDS_SEDI_SW9_6.13