



**REVETMAX™**  
FLEXIBLE REVETMENT

## Specification Sheet – ShoreMax® Transition Mat

### DESCRIPTION

The ShoreMax transition protection mat shall be a resilient rubber mat with surface texture and multi-nib backing. It shall have a large hole drainage system with aperture openings approximately 0.88 in (2.24 cm) in diameter. ShoreMax mat is a transition mat used as biotechnical replacement for hard armor. ShoreMax mat is mechanically anchored and is a flexible matting that can be linked together. ShoreMax mat can provide erosion control in highly erosive areas, including shorelines, and can be used in conjunction with rolled erosion control products.

#### Material Content

<b>Matting</b>	100% UV-stabilized natural rubber	2.65 lbs/sf (12.82 kg/sm)
<b>Color</b>	Dark green or tan	

#### Standard Roll Sizes

<b>Width</b>	3.0 ft (1.0 m)
<b>Length</b>	5.0 ft (1.5 m)
<b>Weight ± 10%</b>	39 lbs (17.69 kg)
<b>Area</b>	1.67 sy (1.39 sm)

#### Design Permissible Shear Stress

Underlayment Type and Phase	Maximum Permissible Shear Stress	Maximum Flow Velocity
SC250	Unvegetated	7.5 psf
	Vegetated	10.0 psf
C350	Unvegetated	8.0 psf
	Vegetated	12.0 psf
P550	Unvegetated	8.5 psf
	Vegetated	14.0 psf

Index Property	Test Method	Typical
<b>Thickness</b>	ASTM D6525	0.75 in. (19.0 mm)
<b>Density</b>	ASTM D792	1.628 oz/in <sup>3</sup>
<b>Mass/Unit Area</b>	ASTM D6566	2.65 lb/sf (13.25 kg/sm)
<b>UV Stability</b>	ASTM D4355 /1000 hr	90-100%
<b>Ground Cover</b>	ASTM D6567	79.3%
<b>Light Penetration</b>	ASTM D6567	20.7%
<b>Hardness</b>	ASTM D2240	68
<b>Specific Gravity</b>	ASTM D792	1.566 g/cm <sup>3</sup>
<b>Flexural Rigidity</b>	ASTM D6575	1.97 in-lbs
<b>Tensile Strength - MD</b>	ASTM D6818	612 lbs/ft (9.07 kN/m)
<b>Elongation - MD</b>	ASTM D6818	102%
<b>Tensile Strength - TD</b>	ASTM D6818	560 lbs/ft (8.30 kN/m)
<b>Elongation - TD</b>	ASTM D6818	96%
<b>Biomass Improvement</b>	ASTM D7322	243 %

#### NTPEP ASTM D6460 Large Scale Channel\*

<b>Unvegetated Shear Stress</b>	8.6 psf (412 Pa)
<b>Vegetated Shear Stress</b>	> 12.5 psf (599 Pa)
<b>Unvegetated Velocity</b>	19.5 fps (5.95 m/s)
<b>Vegetated Velocity</b>	> 26.0 fps (7.93 m/s)

\*Testing conducted with ShoreMax installed over P550



800-452-4435  
info@jenhill.com  
www.jenhill.com

**Tensar**  
NORTH AMERICAN GREEN®

Tensar International Corporation  
2500 Northwinds Parkway  
Suite 500  
Alpharetta, GA 30009  
800-TENSAR-1  
tensarcorp.com

Tensar International Corporation warrants that at the time of delivery the product furnished hereunder shall conform to the specification stated herein. Any other warranty including merchantability and fitness for a particular purpose, are hereby executed. If the product does not meet specifications on this page and Tensar is notified prior to installation, Tensar will replace the product at no cost to the customer. **This product specification supersedes all prior specifications for the product described above and is not applicable to any products shipped prior to January 1, 2012.**

©2013, Tensar International Corporation

EC\_RVTMX\_MPDS\_ShoreMax\_6.13